

<b>H</b>	<b>2400</b>	36	31	28	25	23	21	19	18	17	16	15
	<b>2300</b>	37	33	29	26	24	22	20	19	17	16	16
	<b>2200</b>	39	34	30	27	25	23	21	19	18	17	17
	<b>2100</b>	41	36	32	29	26	24	22	20	19	18	17
	<b>2000</b>	43	38	33	30	27	25	23	21	20	19	18
	<b>1900</b>	45	39	35	32	29	26	24	23	21	20	19
	<b>1800</b>	48	42	37	33	30	28	26	24	22	21	20
	<b>1700</b>	50	44	39	35	32	29	27	25	24	22	21
	<b>1600</b>	54	47	42	38	34	31	29	27	25	23	23
	<b>1500</b>	57	50	44	40	36	33	31	29	27	25	24
	<b>1400</b>	●	54	48	43	39	36	33	31	29	27	26
	<b>1300</b>	●	●	51	46	42	38	36	33	31	29	28
	<b>1200</b>	●	●	56	50	45	42	38	36	33	31	30
	<b>1100</b>	●	●	●	55	50	45	42	39	36	34	33
	<b>1000</b>	●	●	●	●	55	50	46	43	40	38	36
<b>900</b>	●	●	●	●	●	56	51	48	44	42	40	
<b>850</b>	●	●	●	●	●	●	54	50	47	44	43	
	<b>700</b>	<b>800</b>	<b>900</b>	<b>1000</b>	<b>1100</b>	<b>1200</b>	<b>1300</b>	<b>1400</b>	<b>1500</b>	<b>1600</b>	<b>1650</b>	
	<b>L</b>											

## ANWENDUNGSBEREICHE

**Maximales Schiebflügelgewicht 150 Kg**

- Verwendbar bis max. Glasstärke 59 mm
- 20 Verwendbar bis zur angegebenen Glasstärke (z.B. 20 mm)

ANM: Die Glasstärkenangabe bezieht sich auf die Stärke von Vollglas.