



## CAMPO DI APPLICAZIONE

Peso massimo dell' anta 100 Kg

|      |     |     |     |     |     |     |     |     |      |      |      |      |      |      |      |      |
|------|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|
| 2700 | 38  | 34  | 27  | 26  | 22  | 19  | 18  | 17  | 15   | 13   | 12   | 11   | 10   | 9    | 9    | 8    |
| 2600 | 40  | 35  | 28  | 27  | 23  | 20  | 18  | 17  | 15   | 14   | 12   | 11   | 10   | 10   | 9    | 8    |
| 2500 | 42  | 37  | 30  | 28  | 24  | 21  | 19  | 18  | 16   | 14   | 13   | 12   | 11   | 10   | 9    | 9    |
| 2400 | 44  | 39  | 31  | 30  | 26  | 22  | 20  | 19  | 17   | 15   | 14   | 13   | 11   | 11   | 10   | 9    |
| 2300 | 46  | 41  | 32  | 31  | 27  | 23  | 21  | 20  | 18   | 16   | 14   | 13   | 12   | 11   | 10   | 10   |
| 2200 | 48  | 43  | 34  | 33  | 28  | 24  | 22  | 21  | 19   | 17   | 15   | 14   | 13   | 12   | 11   | 10   |
| 2100 | •   | 45  | 36  | 35  | 30  | 26  | 24  | 22  | 20   | 18   | 16   | 15   | 13   | 12   | 12   | 11   |
| 2000 | •   | 48  | 38  | 37  | 32  | 27  | 25  | 23  | 21   | 19   | 17   | 15   | 14   | 13   | 12   | 11   |
| 1900 | •   | •   | 40  | 39  | 33  | 29  | 26  | 25  | 22   | 20   | 18   | 16   | 15   | 14   | 12   | 11   |
| 1800 | •   | •   | 43  | 41  | 36  | 30  | 28  | 26  | 23   | 21   | 19   | 17   | 16   | 14   | 12   | 11   |
| 1700 | •   | •   | 46  | 44  | 38  | 32  | 30  | 28  | 25   | 22   | 20   | 19   | 16   | 14   | 12   | 11   |
| 1600 | •   | •   | 49  | 47  | 41  | 35  | 32  | 30  | 27   | 24   | 22   | 19   | 16   | 14   | 12   | 11   |
| 1500 | •   | •   | •   | •   | 44  | 37  | 35  | 33  | 29   | 26   | 23   | 20   | 16   | 14   | 12   | 10   |
| 1400 | •   | •   | •   | •   | 47  | 40  | 37  | 35  | 31   | 28   | 23   | 20   | 16   | 14   | 12   | 10   |
| 1300 | •   | •   | •   | •   | 44  | 41  | 38  | 34  | 29   | 23   | 20   | 16   | 14   | 12   | 9    |      |
| 1200 | •   | •   | •   | •   | 48  | 45  | 42  | 35  | 29   | 23   | 20   | 16   | 13   | 10   | 7    |      |
| 1100 | •   | •   | •   | •   | 49  | 45  | 36  | 29  | 23   | 20   | 15   | 11   | 7    | 5    |      |      |
| 1000 | •   | •   | •   | •   | •   | 45  | 36  | 29  | 23   | 17   | 11   | 8    | 5    | X    |      |      |
| 900  | •   | •   | •   | •   | •   | 46  | 36  | 28  | 19   | 13   | 8    | 4    | X    | X    |      |      |
| 800  | •   | •   | •   | •   | •   | 46  | 34  | 22  | 13   | 7    | X    | X    | X    | X    |      |      |
| 700  | •   | •   | •   | •   | •   | 41  | 25  | 14  | 6    | X    | X    | X    | X    | X    |      |      |
|      | 455 | 500 | 600 | 620 | 700 | 800 | 855 | 900 | 1000 | 1100 | 1205 | 1300 | 1405 | 1500 | 1600 | 1700 |

Peso massimo dell' anta 130 Kg con kit di rinforzo (art. 3010.718R/L)

|      |     |     |     |     |     |     |     |     |      |      |      |      |      |      |      |      |
|------|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|
| 2700 | •   | 45  | 36  | 35  | 30  | 26  | 24  | 22  | 20   | 18   | 16   | 15   | 14   | 13   | 12   | 11   |
| 2600 | •   | 47  | 38  | 36  | 31  | 27  | 25  | 23  | 21   | 19   | 17   | 15   | 14   | 13   | 12   | 11   |
| 2500 | •   | •   | 40  | 38  | 33  | 28  | 26  | 24  | 22   | 19   | 18   | 16   | 15   | 14   | 12   | 11   |
| 2400 | •   | •   | 41  | 40  | 34  | 29  | 27  | 26  | 23   | 20   | 18   | 17   | 15   | 14   | 12   | 11   |
| 2300 | •   | •   | 43  | 42  | 36  | 31  | 28  | 27  | 24   | 21   | 19   | 18   | 16   | 14   | 12   | 11   |
| 2200 | •   | •   | 46  | 44  | 38  | 32  | 30  | 28  | 25   | 22   | 20   | 19   | 16   | 14   | 12   | 11   |
| 2100 | •   | •   | 48  | 46  | 40  | 34  | 32  | 30  | 26   | 24   | 21   | 19   | 16   | 14   | 12   | 11   |
| 2000 | •   | •   | •   | 49  | 42  | 36  | 33  | 31  | 28   | 25   | 23   | 19   | 16   | 14   | 12   | 11   |
| 1900 | •   | •   | •   | •   | 45  | 38  | 35  | 33  | 29   | 26   | 23   | 19   | 16   | 14   | 12   | 11   |
| 1800 | •   | •   | •   | •   | 47  | 40  | 37  | 35  | 31   | 28   | 23   | 19   | 16   | 14   | 12   | 11   |
| 1700 | •   | •   | •   | •   | •   | 43  | 40  | 38  | 33   | 28   | 23   | 19   | 16   | 14   | 12   | 11   |
| 1600 | •   | •   | •   | •   | •   | 46  | 43  | 40  | 35   | 28   | 23   | 19   | 16   | 14   | 12   | 11   |
| 1500 | •   | •   | •   | •   | •   | 46  | 43  | 35  | 28   | 23   | 20   | 16   | 14   | 12   | 10   |      |
| 1400 | •   | •   | •   | •   | •   | •   | 45  | 35  | 28   | 23   | 20   | 16   | 14   | 12   | 10   |      |
| 1300 | •   | •   | •   | •   | •   | •   | 45  | 35  | 29   | 23   | 20   | 16   | 14   | 12   | 9    |      |
| 1200 | •   | •   | •   | •   | •   | •   | 45  | 35  | 29   | 23   | 20   | 16   | 13   | 10   | 7    |      |
| 1100 | •   | •   | •   | •   | •   | •   | 45  | 36  | 29   | 23   | 20   | 15   | 11   | 7    | 5    |      |
| 1000 | •   | •   | •   | •   | •   | •   | 45  | 36  | 29   | 23   | 17   | 11   | 8    | 5    | X    |      |
| 900  | •   | •   | •   | •   | •   | •   | 46  | 36  | 28   | 19   | 13   | 8    | 4    | X    | X    |      |
| 800  | •   | •   | •   | •   | •   | •   | 46  | 34  | 22   | 13   | 7    | X    | X    | X    | X    |      |
| 700  | •   | •   | •   | •   | •   | •   | 41  | 25  | 14   | 6    | X    | X    | X    | X    | X    |      |
|      | 455 | 500 | 600 | 620 | 700 | 800 | 855 | 900 | 1000 | 1100 | 1205 | 1300 | 1405 | 1500 | 1600 | 1700 |

- Eseguitibile con spessore max. del vetro di mm. 50
  - 20: eseguitibile con spessore max. del vetro (esempio mm 46)
  - X Non eseguitibile
- NOTA: lo spessore del vetro si riferisce allo spessore del materiale senza camera d' aria

