

Pieces needed for realizing a window/door, following L and H dimensions

[illegible]

APPLICATION FIELD

Casement max. weight 100 Kg.

H	2800	•	44	32	26	22	18	16	14	13	11	10	9	9
	2700	•	46	34	27	23	19	17	15	13	12	11	10	9
	2600	•	48	36	28	24	20	17	15	14	12	11	10	10
	2500	•	•	37	30	25	21	18	16	14	13	12	11	10
	2400	•	•	39	31	26	22	19	17	15	14	12	11	10
	2300	•	•	41	33	27	23	20	18	16	14	13	12	11
	2200	•	•	43	34	28	24	21	19	17	15	14	13	12
	2100	•	•	46	36	30	26	22	20	18	16	14	13	12
	2000	•	•	48	38	32	27	24	21	19	17	15	14	13
	1900	•	•	•	41	34	29	25	22	20	18	16	15	14
	1800	•	•	•	43	36	31	27	23	21	19	17	16	14
	1700	•	•	•	46	38	33	28	25	22	20	18	16	14
	1600	•	•	•	49	41	35	30	27	24	22	19	16	14
	1500	•	•	•	•	44	38	33	29	26	23	20	16	14
L	1400	•	•	•	•	48	41	35	31	28	23	20	16	14
	1300	•	•	•	•	•	44	38	34	29	24	20	16	14
	1200	•	•	•	•	•	48	42	36	29	24	20	17	13
	1100	•	•	•	•	•	•	45	36	29	24	20	15	11
	1000	•	•	•	•	•	•	46	36	29	24	17	12	8
	900	•	•	•	•	•	•	46	36	28	19	13	8	4
	800	•	•	•	•	•	•	47	34	22	14	8	3	X
	700	•	•	•	•	•	•	42	25	14	6	X	X	X
	350													
	400													
	500													
	600													
	700													
	800													
	900													
	1000													
	1100													
	1200													
	1300													
	1400													
	1500													

Casement max. weight 70 Kg (without supplementary screws)

H	2800	35	29	22	17	14	12	10	9	8	7	7	6	6
	2700	37	31	23	18	15	13	11	10	9	8	7	6	6
	2600	39	32	24	19	16	13	11	10	9	8	7	7	6
	2500	40	34	25	20	16	14	12	11	9	8	8	7	6
	2400	42	35	26	21	17	15	13	11	10	9	8	7	7
	2300	45	37	29	22	18	15	13	12	10	9	8	8	7
	2200	47	39	29	23	19	16	14	12	11	10	9	8	8
	2100	•	41	31	24	20	17	15	13	12	10	9	9	8
	2000	•	44	32	26	21	18	16	14	12	11	10	9	8
	1900	•	46	34	27	23	19	17	15	13	12	11	10	9
	1800	•	49	37	29	24	20	18	16	14	13	11	10	10
	1700	•	•	39	31	26	22	19	17	15	13	12	11	10
	1600	•	•	42	33	28	23	20	18	16	14	13	12	11
	1500	•	•	45	36	30	25	22	19	17	16	14	13	12
	1400	•	•	49	39	32	27	24	21	19	17	15	14	13
L	1300	•	•	•	42	35	30	26	23	20	18	17	15	14
	1200	•	•	•	47	38	33	28	25	22	20	18	17	13
	1100	•	•	•	•	43	36	32	28	25	22	20	15	11
	1000	•	•	•	•	48	41	35	31	28	24	17	12	8
	900	•	•	•	•	•	46	40	35	28	19	13	8	4
	800	•	•	•	•	•	•	46	34	22	14	8	3	X
	700	•	•	•	•	•	41	25	14	6	X	X	X	X
	350													
	400													
	500													
	600													
	700													
	800													
	900													
	1000													
	1100													
	1200													
	1300													
	1400													
	1500													

• Feasible with max. glass thickness of mm.50
46: feasible with max. glass thickness indicated (ex. mm. 46)
X: Not feasible.
NOTE: glass thickness refers to the thickness of the material without air space

